

Takht-e-Jamshid Pars Assalouyeh

Petrochemical Company

General Purpose Polystyrene (GPPS)				
TYPICAL DATA SHEET	GRADE	<u>www.tjpa-pc.com</u>		
	TJPS-G1551 (Normal flow)	IRAN/ASSALOUYEH/PETROCHEMICAL COMPANY/ TEL: 077-37324159		

This grade is high strength & high cycle polystyrene.

Main Applications:

Thin walled food Containers, Medical ware (petri dishes etc), Office stationary, housewares, etc.

TECHNICAL SPECIFICATION

PROPERTIES	UNIT	VALUE	STANDARD	
Tensile Strength (Yield)	(kg/cm²)	440	D-638	
Tensile Modulus of Elasticity	(kg/cm²)	2.6×10 ⁴	D-638	
Izod Impact Strength (notched,t=6.4 mm)	(kg-cm/cm)	2. 4	D-256	
Vicat Softening Point (50°C/hr ,1000 g)	(°C)	92	D-1525	
Melt Index (200°C , 5000 g)	(g/10 min)	9	D-1238	

^{*}All above mentioned data are typical values and not to be construed as real specifications. Users should confirm results by their own tests. Which is included MFI and Vicat.

Site: Next to Styrene park, Outset of Phase II Petrochemical Zone ASSALOUYEH, IRAN

Tel: +98 (77) 3732 4161 Fax: +98 (77) 3732 4079

Head Office: No. 12, second floor,

Gandhi **14**th str. , Valiasr Ave. TEHRAN, IRAN

Tel: +98 (21) 8819 5919 Fax: +98 (21) 8829 5719 www.tjpa-pc.com

info@tjpa-pc.com

^{**} TJPAPC Guaranteed items are MFI and Vicat .